


Installation

Phenolic Privacy Restroom Partitions, Floor-Mounted with Overhead Brace – Series 400



**For Standard Height
Doors and Panels Only**

Table of Contents

Safety Information	2
Supplies Required	3
Hardware Provided	3
Example of Submittal Drawing	3
Door Descriptions & Part Numbers	4
Pilaster Descriptions & Part Numbers	5
Pilaster Configurations & Part Numbers	6
Pilaster Configurations & Wall Hung Part Numbers	7
Layout Dimensions for Brackets	8–9
Mounting Brackets to Wall	10
Leveling Screws to Pilaster	11
Mounting Brackets to Pilaster	12–13
Pilaster Mounting Hardware	13
Pilasters and Panels	14–15
Wall-Hung Pilasters	16–17
Pilaster Shoes	18
Headrail	19
Hinges	20–21
Door Hardware	22–27
Urinal Screens	28–29



Read the instructions in this manual before beginning installation. Save these instructions and refer to them for inspection, maintenance, and troubleshooting information.

For questions regarding the operation, installation or maintenance of this product, visit bradleycorp.com or call 800.BRADLEY (800.272.3539).

Product warranties and parts information may also be found on our website at bradleycorp.com.



Safety Information

Warning

Before beginning installation, make sure that the wall and floor backing are adequate to support the secure mounting of the toilet compartment units.

Partitions are extremely heavy and may require more than one person to position and install.

Failure to comply with these instructions may result in personal injury and/or property damage and will void the partition warranty.

Caution

Personal protective equipment (PPE) is required during the installation and maintenance of this product.

Notice

To prevent warping, always lay the material flat. Do not lean the material against the wall or stack unevenly.

Make sure all floors and walls are clean and smooth. Remove loose impediments, such as protruding nails and other debris which could affect installation.

To minimize break-out, always use a support block when drilling through the material.

Carefully remove components from skid, do not drag.

Important

Review your partition layout drawings and verify the number of stalls and components before beginning installation. All components are labeled with their corresponding part number. Descriptions and part numbers for doors, pilasters, and pilaster configurations are listed on pages 4–7 for easy identification.

Read this installation manual completely to ensure proper installation, then file it with the owner or maintenance department.

This installation manual provides instruction for the assembly of normal partition configurations and standard components.


Non-standard configurations or components including but not limited to curved or angled walls, partial walls, oversized panels, or modified hardware are not covered in this manual. Compliance and conformity to local codes and ordinances is the responsibility of the installer.

Separate parts from packaging and make sure all parts are accounted for before discarding packaging material. If any parts are missing, do not begin installation until you obtain the missing parts.


Supplies Required

- Chalk line and pencil
- Tape measure and 4' level
- Jigsaw (or hacksaw) and circular saw
- Two spring clamps
- 9/64", 11/64", 7/32", 15/64", 1/4", and 17/64" drill bits
- Power drill or screw gun with drill bit extension
- 15/16" ceramic tile and masonry drill bit
- Hammer drill
- Spacer, 12" (305) high and strong enough to support weight of panel and 1/8" (3) for gap between door and pilaster
- Isopropyl alcohol


Hardware Provided




9/32" x 5/8"
Washer Flat
P10-449



5/16" x 1-1/2"
Hex Head
Lag Screw
FAST-S008



#14-16 Plastic
Anchor
FAST-T373



#10-12 x 1"
Plastic Anchor
FAST-T381



#14 x 2"
Button-Head
Sheet Metal Screw
Torx-T27 Drive
FAST-P002



#14 x 5/8"
Button-Head
Sheet Metal Screw
Torx-T27 Drive
FAST-S0016



#10 x 5/8"
Button-Head
Sheet Metal Screw
Torx-T27 Drive
FAST-S0019



#10 x 1"
Button-Head
Sheet Metal Screw
Torx-T27 Drive
FAST-S0028



#10 x 2"
Flat-Head
Sheet Metal Screw
Torx-T25 Drive
FAST-S0046



#10-24 x 3/8"
Button-Head
Machine Screw
Torx-T27 Drive
FAST-S0015



#10-24 x 1/2"
Button-Head
Machine Screw
Torx-T27 Drive
FAST-S0018



#10-24 x 3/4"
Button-Head
Shoulder Screw
Torx-T27 Drive
FAST-P004




#10 x 1/2"
Button-Head
Cap Screw
Torx-T27 Drive
FAST-S0045



#10-24 x 1/2"
Button-Head
Barrel Nut
Torx-T27 Drive
FAST-S0017




#10-24 x 2"
Flat-Head
Machine Screw
Torx-T25 Drive
FAST-S0027



Vibration
Dampening Strip,
.065 x .250 x 1",
2 Strip Set
HDWC-00566-58


Example of Submittal Drawing

(mm)



Door Descriptions & Part Numbers

- ☑ Part number logic and descriptions for doors are based on in-swinging doors. The door swing and handedness is determined by facing the stall from the outside.
- ☑ RH indicates right-hand inswing or left-hand outswing. LH indicates left-hand inswing or right-hand outswing.
- ☑ Phenolic privacy doors come with pre-installed inserts for attaching the hinges.





Pilaster Descriptions & Part Numbers



Part number logic and descriptions for pilasters are based on in-swinging doors. The pilaster handedness is based off of the door hinge/latch, as determined by facing the stall from the outside.






Phenolic privacy pilasters come with pre-installed inserts for attaching the hinges (where applicable).



C480-XXNSIAH-XXXX
No-Site, Left Latch Out &
Left Hinge In /
Right Hinge Out &
Right Latch In

C480-XXNSIBH-XXXX
No-Site, Right Hinge In &
Right Latch Out /
Left Latch In &
Left Hinge Out



C480-XXNIWRH-XXXX C480-XXNSALH-XXXX
No-Site Wall, Right Hinge In /
Left Hinge Out No-Site Alcove,
Left Latch In / Right Latch Out

C480-XXNSARH-XXXX C480-XXNIWLH-XXXX
No-Site Alcove, Right Latch In /
Left Latch Out No-Site Wall,
Left Hinge In / Right Hinge Out



Pilaster Configurations & Part Numbers



Part number logic and descriptions for pilasters are based on in-swinging doors. Pilaster orientation is shown as inswing in the following illustration. The pilaster handedness is based off of the door hinge/latch, as determined by facing the stall from the outside.




Phenolic privacy pilasters come with pre-installed inserts for attaching the hinges (where applicable).




C480-XXNSALH-XXXX
No-Site Alcove,
Left Latch In /
Right Latch Out




C480-XXNSARH-XXXX
No-Site Alcove,
Right Latch In /
Left Latch Out




C480-XXNSRH-XXXX
No-Site, Left Latch
Out & Right Latch In



C480-XXNSLH-XXXX
No-Site, Left Latch In &
Right Latch Out




C480-XXNS-XXXX
No-Site, Left Latch In &
Right Latch In / Left Latch
Out & Right Latch Out




C480-XXNIWRH-XXXX
No-Site Wall,
Right Hinge In /
Left Hinge Out




C480-XXNIWLH-XXXX
No-Site Wall,
Left Hinge In /
Right Hinge Out



C480-XXNSIAH-XXXX
No-Site, Left Latch Out &
Left Hinge In / Right Hinge
Out & Right Latch In



C480-XXNSIBH-XXXX
No-Site, Right Hinge In &
Right Latch Out / Left Latch
In & Left Hinge Out




C480-XXNSILH-XXXX
No-Site, Left Latch In &
Left Hinge In / Right Hinge
Out & Right Latch Out




C480-XXNSIRH-XXXX
No-Site, Right Hinge In &
Right Latch In / Left Latch Out
& Left Hinge Out



C480-XXNI2RH-XXXX
No-Site, Right Hinge In
& Left Hinge Out




C480-XXNI2LH-XXXX
No-Site, Right Hinge Out
& Left Hinge In




C480-XXNI2CH-XXXX
No-Site, Right Hinge In &
Left Hinge In / Right Hinge
Out & Left Hinge Out

Pilaster Configurations & Wall Hung Part Numbers


- Part number logic and descriptions for pilasters are based on in-swinging doors. Pilaster orientation is shown as inswing in the following illustration. The pilaster handedness is based off of the door hinge/latch, as determined by facing the stall from the outside.
- RH indicates right-hand inswing or left-hand outswing. LH indicates left-hand inswing or right-hand outswing.
- Phenolic privacy pilasters come with pre-installed inserts for attaching the hinges (where applicable).



C758-XXNSALH-XXXX
No-Site Alcove,
Left Latch In /
Right Latch Out



C758-XXNSARH-XXXX
No-Site Alcove,
Right Latch In /
Left Latch Out



C758-XXNIWRH-XXXX
No-Site Wall,
Right Hinge In /
Left Hinge Out



C758-XXNIWLH-XXXX
No-Site Wall,
Left Hinge In /
Right Hinge Out



C770-XXNSALH-XXXX
No-Site Alcove,
Left Latch In /
Right Latch Out



C770-XXNSARH-XXXX
No-Site Alcove,
Right Latch In /
Left Latch Out



C770-XXNIWRH-XXXX
No-Site Wall,
Right Hinge In /
Left Hinge Out



C770-XXNIWLH-XXXX
No-Site Wall,
Left Hinge In /
Right Hinge Out

1 Layout Dimensions - Stirrup Brackets (Standard)


 When installing the partition components, consult the applicable Mills Partition submittal drawing for compartment layout dimensions.

A Pilaster Centerline: Measure from the back wall forward to the face of the compartment, subtract 3/8" (10) and mark this location on the floor ("A"). Mark the same measurement on the opposite end of your layout ("A1") and draw a straight line connecting both marks.

For Freestanding (FS) Partitions: Refer to submittal drawings and determine the approximate location of the outside panels. Establish dimensions "A" and "A1" as explained above.

C Draw a plumb line on all walls from each pilaster and panel centerline. From the highest point in the room, measure 19" (483) and 63" (1600) from the floor and place a mark on the pilaster/panel plumb line. These marks represent the hole center line of the stirrup brackets. Use a level to transfer that mark to all other plumb lines ("C").

B Panel Centerline: Measure the stall width across the back wall and place a mark at the base of the rear wall ("B"). Repeat this step for each panel, starting each measurement from the last panel centerline ("B1").



1a Layout Dimensions - 3 Stirrup Brackets (Optional)


 When installing the partition components, consult the applicable Mills Partition submittal drawing for compartment layout dimensions.

A Pilaster Centerline: Measure from the back wall forward to the face of the compartment, subtract 3/8" (10) and mark this location on the floor ("A"). Mark the same measurement on the opposite end of your layout ("A1") and draw a straight line connecting both marks.

For Freestanding (FS) Partitions: Refer to submittal drawings and determine the approximate location of the outside panels. Establish dimensions "A" and "A1" as explained above.

C Draw a plumb line on all walls from each pilaster and panel centerline. From the highest point in the room, measure 19" (483), 43" (1092) and 63" (1600) from the floor and place a mark on the pilaster/panel plumb line. These marks represent the hole center line of the stirrup brackets. Use a level to transfer that mark to all other plumb lines ("C").

B Panel Centerline: Measure the stall width across the back wall and place a mark at the base of the rear wall ("B"). Repeat this step for each panel, starting each measurement from the last panel centerline ("B1").




1b Layout Dimensions - Continuous Brackets (Optional)

When installing the partition components, consult the applicable Mills Partition submittal drawing for compartment layout dimensions.

A **Pilaster Centerline:** Measure from the back wall forward to the face of the compartment, subtract 3/8" (10) and mark this location on the floor ("A"). Mark the same measurement on the opposite end of your layout ("A1") and draw a straight line connecting both marks.

For Freestanding (FS) Partitions: Refer to submittal drawings and determine the approximate location of the outside panels. Establish dimensions "A" and "A1" as explained above.

C Draw a plumb line on all walls from each pilaster and panel centerline. From the highest point in the room, measure from the floor and place a mark on the pilaster/panel plumb line at 12-1/2" (318). Use a level to transfer that mark to all other plumb lines ("C").



B **Panel Centerline:** Measure the stall width across the back wall and place a mark at the base of the rear wall ("B"). Repeat this step for each panel, starting each measurement from the last panel centerline ("B1").


2 Stirrup Brackets to Wall (Standard)

- ✓ On end panel and pilaster applications, position the bracket with the ear facing toward the inside of the stall.
- ✓ Pilaster bracket is shown here. 3/4" (19) opening brackets are for pilasters and 1/2" (13) opening brackets are for panels.

A Place the center of each stirrup bracket at the established level line. Center the bracket opening on the pilaster/panel plumb line.

B Using the bracket as a template, mark the hole locations on the wall. Remove the bracket and drill a Ø5/16" hole (min. 2" (51) deep) at each hole location.

C Insert the plastic anchors in all holes and secure the brackets to the wall with the #14 x 2" screws provided.




2a Continuous Stainless Steel Brackets to Wall (Optional)

- ✓ On pilaster applications, position the bracket with the ear facing toward the inside of the stall.
- ✓ Pilaster bracket shown here; 'Ear' brackets (3/4" (19) opening) are for pilasters and U-brackets (1/2" (13) opening) are for panels.
- ✓ Brackets are used as templates, but since the hole patterns may be different, the brackets may not be interchangeable.

A Place the bottom of each continuous bracket at the established level line. Center the bracket opening on the pilaster/panel plumb line.

B Using the bracket as a template, mark the hole locations on the wall. Remove the bracket and drill a Ø5/16" hole (min. 2" (51) deep) at each hole location.

C Insert the plastic anchors in all holes and secure the brackets to the wall with the #14 x 2" screws provided.



3 Leveling Screws to Pilaster




A notch will be present on one end of the pilaster to indicate that it is the bottom.

3"-16" Pilaster: Center and drill a $\text{Ø}17/64$ " pilot hole, 1-1/2" (38) deep.


A 18"-24" Pilaster: Drill (2) $\text{Ø}17/64$ " pilot holes, 1-1/2" (38) deep. Holes should be 2" (51) off each end of the pilaster.

B Use leveling screw(s) to adjust height of pilaster.



4 Stirrup Brackets to Pilaster (Standard) and 3-Stirrup Brackets to Pilaster (Optional)

Refer to the submittal drawing to locate the split dimension and layout location of each marked pilaster.




A Measure down from the top of the pilaster and place a mark on the pilaster split centerline at the dimensions shown for the respective bracket.

Pilaster shown is for reference only. Actual pilaster varies depending on application.

B Place the center of each stirrup bracket at the marks made in Step A. Center the bracket opening on the pilaster split centerline. Using the bracket as a template, mark the hole locations on the pilaster. Remove the bracket and drill a $\text{Ø}15/64$ " pilot hole, 5/8" (16) deep at each location.

C Secure the stirrup brackets to the pilasters using the #14 x 5/8" screws provided.




* For third stirrup bracket option only.

4a Continuous Brackets to Pilaster (Optional)

Refer to the submittal drawing to locate the split dimension and layout location of each marked pilaster.

Brackets are used as templates, but since the hole patterns may be different, the brackets may not be interchangeable.




A Measure down from the top of each pilaster and place a mark on the pilaster split centerline at dimensions shown.

Pilaster shown is for reference only. Actual pilaster varies depending on application.

B Place the continuous bracket between each established level line. Center the bracket opening on the pilaster split centerline. Using the bracket as a template, mark the hole locations on the pilaster. Remove the bracket and drill a $\text{Ø}15/64$ " pilot hole, 5/8" (16) deep at each location.

C Secure the continuous bracket to the pilasters using the #14 x 5/8" screws provided.



4b Stirrup Alcove Brackets to Pilaster (Standard) and 3-Stirrup Alcove Brackets or Continuous Alcove Brackets to Pilaster (Optional)


 Refer to the submittal drawing for the layout location of each alcove pilaster

A Measure down from the top of the pilaster and place a mark at dimensions shown for the respective bracket situation.

B **Stirrup:** Position the center of each bracket at the marks made in Step A.
Continuous: Center the bracket between each mark made in Step A.


C Using the bracket as a template, mark the hole locations on the pilaster. Remove the bracket and drill Ø1/4" holes through the pilaster at each location.

D **Stirrup:** Secure the brackets to the pilaster using the #10-24 x 1/2" barrel nuts and #10-24 x 3/4" shoulder screws provided.
Continuous: Secure the brackets to the pilaster using the #10-24 x 1/2" barrel nuts and #10-24 x 1/2" shoulder screws provided.




5 Pilaster Mounting Hardware

A Starting with the pilaster closest to the wall, measure and mark the pilaster and door widths on the pilaster centerline. Make sure to leave the appropriate gap between the wall and the pilaster. Place corresponding shoe on the pilaster centerline and center between the marks.



B Using the shoe as a template, mark the hole locations on the floor. Remove the shoe and drill Ø5/16" holes (min. 2" (51) deep) into the floor. Make sure the holes are free of dirt and debris.

C Insert plastic anchors into the holes and secure the shoe to the anchors using the 9/32" x 5/8" flat washer and #14 x 2" screws provided.



6 Pilasters and Panels with Stirrup Brackets (Standard)


- Pilasters located at walls should be mounted first. Start at one end and install a panel, then a pilaster. Continue alternating until installation is complete. When installing in an alcove or in-corner, use an alcove bracket to secure the pilaster to the panel.
- Check to make sure the pilasters are plumb and level to each other. The pilaster height can be adjusted with the leveling screw that was placed at the bottom of the pilaster (see page 11 for attaching leveling screw).
- 2-stirrup bracket set is shown below.

Pilasters at Wall

- When installing pilasters at walls, the gaps range from 1/2" to 1-1/4" (13 to 32). Refer to your submittal drawing for your gap sizes.

A Place the pilaster into the shoe secured to the floor while at the same time placing it within the wall brackets.

B Using the bracket as a template, drill $\text{\O}1/4"$ holes through the pilaster at each pilaster bracket hole. Secure the pilaster to the bracket using the #10-24 x 1/2" barrel nuts and #10-24 x 3/4" shoulder screws provided.




Pilasters with Panels

- Refer to your submittal drawing and leave the appropriate gaps. Standard gap is 1" (25) between the panel and wall and 1/2" (13) between the panel and pilaster.

A Place the panel on the spacer and insert the panel into the wall brackets.

B Place the pilaster into the shoe secured to the floor while at the same time placing the brackets around the panel.

C Using the bracket as a template, drill $\text{\O}1/4"$ holes through the panel at each panel bracket hole. Secure the panel to the bracket using the #10-24 x 1/2" barrel nuts and #10-24 x 1/2" shoulder screws provided.



6a Pilasters and Panels with Stainless Steel Continuous Brackets (Optional)


- Pilasters located at walls should be mounted first. Start at one end and install a panel, then a pilaster. Continue alternating until installation is complete. When installing in an alcove or in-corner, use an alcove bracket to secure the pilaster to the panel.
- Check to make sure the pilasters are plumb and level to each other. The pilaster height can be adjusted with the leveling screw that was placed at the bottom of the pilaster (see page 11 for attaching leveling screw).

Pilasters at Wall

- When installing pilasters at walls, the gaps range from 1/2" to 1-1/4" (13 to 32). Refer to your submittal drawing for your gap sizes.

A Place the pilaster into the shoe secured to the floor while at the same time placing it within the wall bracket.

B Using the bracket as a template, drill Ø1/4" holes through the pilaster at each pilaster bracket hole. Secure the pilaster to the bracket using the #10-24 x 1/2" barrel nuts and #10-24 x 1/2" shoulder screws provided.




Pilasters with Panels

- Refer to your submittal drawing and leave the appropriate gaps. Standard gap is 1" (25) between the panel and wall and 1/2" (13) between the panel and pilaster.

A Place the panel on the spacer and insert the panel into the wall bracket.

B Place the pilaster into the shoe secured to the floor while at the same time placing the bracket around the panel.

C Using the bracket as a template, drill Ø1/4" holes through the panel at each panel bracket hole. Secure the panel to the bracket using the #10-24 x 1/2" barrel nuts and #10-24 x 3/8" machine screws provided.




6b Wall-Hung Pilasters (58" or 69-3/8") – Stirrup Brackets (Optional)

- ✓ See Step 2 for instructions on mounting the stirrup brackets to a wall.
- ✓ See Step 4 for instructions on mounting the stirrup brackets to a pilaster.
- ✓ To establish level line, from the highest point in the room, measure 12" Ref. (305) from the floor. Use a level to transfer this mark to the pilaster plumb line.
- ✓ Hinged wall-hung pilasters shown in (2) different lengths for visual reference.
- ✓ 2-stirrup bracket set is shown below.

Pilasters at Wall

A Slide the wall-hung pilaster into the stirrup brackets and align with the established level line. Refer to the submittal drawing and adjust to meet the specified dimension.


B Using the bracket as a template, drill $\text{Ø}1/4"$ holes through the pilaster at each pilaster bracket hole. Secure the pilaster to the bracket using the #10-24 x 1/2" barrel nuts and #10-24 x 3/4" shoulder screws provided.



Pilasters at Pilasters

A Slide the wall-hung pilaster into the stirrup brackets and align with the established level line. Refer to the submittal drawing and adjust to meet the specified dimension.

B Using the bracket as a template, drill $\text{Ø}1/4"$ holes through the pilaster at each pilaster bracket hole. Secure the pilaster to the bracket using the #10-24 x 1/2" barrel nuts and #10-24 x 3/4" shoulder screws provided.




6c Wall-Hung Pilasters (58" or 69-3/8") – Continuous Stainless Steel Brackets (Optional)

- ✓ See Step 2a for instructions on mounting the continuous stainless steel brackets to a wall.
- ✓ See Step 4a for instructions on mounting the continuous stainless steel brackets to a pilaster.
- ✓ To establish level line, from the highest point in the room, measure 12" Ref. (305) from the floor. Use a level to transfer this mark to the pilaster plumb line.
- ✓ Hinged wall-hung pilasters shown in (2) different lengths for visual reference.

Pilasters at Wall


A Slide the wall-hung pilaster into the continuous bracket and align with the established level line. Refer to the submittal drawing and adjust to meet the specified dimension.

B Using the bracket as a template, drill $\text{Ø}1/4"$ holes through the pilaster at each pilaster bracket hole. Secure the pilaster to the bracket using the #10-24 x 1/2" barrel nuts and #10-24 x 1/2" shoulder screws provided.



58" (1473) Pilaster


69-3/8" (1762) Pilaster



Pilasters at Pilasters


A Slide the wall-hung pilaster into the continuous bracket and align with the established level line. Refer to the submittal drawing and adjust to meet the specified dimension.

B Using the bracket as a template, drill $\text{Ø}1/4"$ holes through the pilaster at each pilaster bracket hole. Secure the pilaster to the bracket using the #10-24 x 1/2" barrel nuts and #10-24 x 1/2" shoulder screws provided.



58" (1473) Pilaster


69-3/8" (1762) Pilaster



7 Pilaster Shoes

A Using the hole in the shoe as a template, drill a $\text{Ø}1/4"$ hole through the pilaster.


B Secure the pilaster to the shoe using the #10-24 x $1/2"$ barrel nut and #10-24 x $3/4"$ shoulder screw provided.




8 Headrail

- ✓ Make sure the pilasters are plumb and that the pilaster has been secured to the shoe. Leave the appropriate door opening between the pilasters as shown on your submittal drawing.
- ✓ The illustrations on this page show mounting hardware and fasteners for a generic application. Refer to your submittals to determine your actual headrail configurations.
- ✓ Some headrail sections may need to be cut to an appropriate size. Refer to your submittals for general headrail placement.
- ✓ Headrail configurations that come to an intersection should meet over a pilaster (see completed headrail assembly view below).


A Place headrail over the top of each pilaster located at the wall and slide it tight against the side wall. Mark the outline of the headrail on the wall and remove the headrail.



B Place the headrail bracket on the outline marked on the wall and mark the locations of the mounting holes. Remove bracket and drill (2) Ø5/16" holes a minimum of 2" (51) deep. Prior to securing to the wall, enlarge the (2) back mounting holes of the bracket to Ø1/4". Secure the bracket to the wall using the #14 x 2" screws and plastic anchors provided.




C Place headrail over the top of the pilasters and slide it tight into the mounting bracket. Use the mounting bracket as a template and drill a Ø7/32" hole through the headrail. Secure the headrail to the mounting bracket using the #10 x 5/8" screws provided.




D Make sure the pilaster is plumb and that the spacing between the pilasters for the doors is the correct dimension. On the back of each pilaster (starting with the first pilaster), drill a Ø7/32" hole through one face of the headrail only.


Using this hole as a template, drill a Ø11/64" pilot hole into the pilaster, 5/8" (16) deep. Secure the headrail to the back of each pilaster using the #10 x 5/8" screws provided.



E For open end applications, cut the headrail to the appropriate length (if required). Attach the bracket to the wall at the correct height (see step B). Attach another bracket to a pilaster with #10 x 5/8" screws at the correct height (see view below). The headrail should be level with any adjacent headrail and should be located directly over the panel. Position each headrail onto the brackets and secure with required fasteners (see step C). Using a rubber mallet, install the headrail end cap.




Completed Headrail Assembly




9 Surface-Mounted Hinges


-  Before installing the hinges, make sure the door openings are the appropriate size, all pilasters are plumb and secured to the shoe, and that the headrail is installed.
-  Refer to your submittal drawings to determine each specific door swing for your application. The door swing is determined by facing the compartment from the outside. The image below can help determine the door swing type.
-  Hinges are mounted to the factory-installed inserts on the doors and pilasters.



A Separate the hinge components and ensure all parts are included as shown.



B Locate the hinge assembly that coincides with the door swing. Arrange the hinge sets as shown.



9 Surface-Mounted Hinges (continued)

- ✓ *The knuckle gap of the top hinge varies based on the cam setting.*
- ✓ *Left-hand outswing door shown.*

C Refer to the hinge diagram and identify the top and bottom hinges. The hinge leaves are configured so that the door cannot be lifted off of the pilaster.

Pilaster - Top & Bottom Hinge Leaf

D Separate the hinge leaves. Align the holes in the leaves that have the plastic bushings with teeth and the cam alignment slots to the threaded inserts in the pilaster. Secure using the 1/4-20 x 1/2" cap screws provided. Hand tighten screws.

E Insert the hinge pin and cam into the top pilaster leaf. The alignment tabs on the cam should fit into the slots on the leaf.

Door - Top Hinge Leaf

F Align the holes in the leaf without teeth to the top threaded inserts in the door, and then secure using the 1/4-20 x 1/2" cap screws provided. Hand tighten screws.

G Lift the door into place. Slide the top door leaf over the top pilaster leaf hinge pin and rest on the spacer (provided by others).

Door - Bottom Hinge Leaf


H Insert the hinge pin into the bottom hinge door leaf and slide it up into the pilaster bottom hinge leaf. Align the holes with the inserts in the door and secure using the 1/4-20 x 1/2" cap screws provided. Hand tighten screws.

I Place 1/8" spacers (by others) between the door and pilaster notch at the top and bottom to achieve a symmetric gap between the door, pilaster on hinge, and latch sides. Torque screws to 80–90 in-lb.


J Adjust the door opening as follows:

- To increase the door opening, lift the door and rotate cam toward the direction of the door, making sure the bushing and cam tabs are aligned.
- To decrease the door opening, lift the door and rotate cam toward the direction of the pilaster, making sure the bushing and cam tabs are aligned.

✓ *The gap between the bottom of the door and the pilaster leaf is needed for rise of the door when opened.*




✓ *The tabs on the cam need to align with the slots in the leaf with has the plastic bushing and teeth.*



10 Door Hardware for Inswing Doors

 Local codes vary from state to state. Check your local codes before installing the door pulls and coat hook.

A From the back side of the door, align the two mounting posts on the slide latch with the holes in the door. Hold or tape in place.



B From the front side of the door, align the black disk with the countersunk holes at top and sides with the holes in the metal handle. Place the longer flat head Phillips drive screws (provided) through the side holes in the black disk, metal handle, and door. Secure to the mounting posts in the slide latch.


C Using the top countersunk hole in the black disk as a template, drill a $\text{Ø}9/64$ " pilot hole, $1/2$ " (13) deep and secure to the door using the small flat head Phillips drive screw (provided).

D Place the square pin into the back of the indicator circle. Verify the red indication color is in the proper position so that red will appear when the latch is in the closed position.

E Slide the square pin through the large center hole in the door and into the slide latch on the other side.

F Again, verify the red indication color is in the proper position to appear when the latch is in the closed position before securing the indicator circle with the small tabs over the black plastic piece.


G With the door in the closed position, place the keeper on the pilaster so the leading edge is $.030$ " (.762) from the pilaster notch and the slide latch moves freely over the keeper. Using the keeper as a template, drill (2) $\text{Ø}15/64$ " pilot holes, $5/8$ " (16) deep. Secure with the #14 x $5/8$ " Torx screws provided.




 When the door latch is correctly installed, the red indicator color should appear when the latch is in the closed position.

10 Door Hardware for Inswing Doors (continued)


H For 34"-36" doors, mark the location for the top hole on the inside face of the door 30-3/4" (781) up from the bottom of 58" tall doors (42-3/4" (1086) above finished floor) and 6-1/2" (165) from the door edge. Drill (2) Ø1/4" holes (spaced 3-1/2" (89) apart) through the door and secure the door pulls to the door as shown with the #10-24 x 2" flat machine screws provided.



Place the coat hook 3" (76) down from the top and 3" (76) from the latch side of the door (hook goes on the inside face of the door). Using the hook as a template, drill (2) Ø11/64" pilot holes, 5/8" (16) deep. Secure with the #10 x 5/8" screws provided.



J Clean the strike pilaster notched surface using isopropyl alcohol (by others). Remove a dampening strip from the liner and place the top edge 3" (76) down from the top notch; apply pressure to adhere to the pilaster. Remove the second dampening strip from the liner and place the bottom edge 3" (76) up from the bottom notch, and apply pressure to adhere to the pilaster.




10 Door Hardware for Inswing Doors (continued)**Flat Strike at Wall – Inswing**

K With the door in the closed position, place the non-notched edge of the flat strike against the wall. The notched edge of the door should fit into the notch on the flat strike. The top edge of the flat strike and door should align along with the front faces.

L Using the flat strike as a template, mark the hole locations on the wall. Remove the flat strike and drill a $\text{Ø}1/4"$ hole (min. 2" (51) deep) at each hole location.

M Insert the plastic anchors in all of the holes and secure the flat strike to the wall using the #10 x 2" screws provided.

N Refer to Step G for installing the keeper and Step J for installing the dampening strip.


**Flat Strike at Pilaster – Inswing**

O With the door in the closed position, place the non-notched edge of the flat strike against the pilaster. The notched edge of the door should fit into the notch on the flat strike. The top edge of the flat strike and door should align along with the front faces.

P Using the flat strike as a template, mark the hole locations on the pilaster. Remove the flat strike and drill a $\text{Ø}11/64"$ hole (min. 1/2" (13) deep) at each hole location.

Q Secure the flat strike to pilaster wall using the #10 x 1" screws provided.


R Refer to Step G for installing the keeper and Step J for installing the dampening strip.



10a Door Hardware for Outswing Doors

Local codes vary from state to state. Check your local codes before installing the door pulls and coat hook.

A From the back side of the door, align the two mounting posts on the slide latch with the holes in the door. Hold or tape in place.



B From the front side of the door, align the black disk with the countersunk holes at top and sides with the holes in the metal handle. Place the longer flat head Phillips drive screws (provided) through the side holes in the black disk, metal handle, and door. Secure to the mounting posts in the side latch.


C Using the top countersunk hole in the black disk as a template, drill a $\text{Ø}9/64$ " pilot hole, 1/2" (13) deep and secure to the door using the small flat head Phillips drive screw (provided).

D Place the square pin into the back of the indicator circle. Verify the red indication color is in the proper position so that red will appear when the latch is in the closed position.

E Slide the square pin through the large center hole in the door and into the slide latch on the other side.

F Again, verify the red indication color is in the proper position to appear when the latch is in the closed position before securing the indicator circle with the small tabs over the black plastic piece.


G With the door in the closed position, place the keeper on the pilaster so the leading edge is .030" (.762) from the pilaster edge and the slide latch moves freely over the keeper. Using the keeper as a template, drill (2) $\text{Ø}15/64$ " pilot holes, 5/8" (16) deep. Secure with the #14 x 5/8" Torx screws provided.




When the door latch is correctly installed, the red indicator color should appear when the latch is in the closed position.

10a Door Hardware for Outswing Doors (continued)


H For 34"-36" doors, mark the location for the top hole on the inside face of the door 30-3/4" (781) up from the bottom of 58" tall doors (42-3/4" (1086) above finished floor) and 6-1/2" (165) from the door edge. Drill (2) Ø1/4" holes (spaced 3-1/2" (89) apart) through the door and secure the door pulls to the door as shown with the #10-24 x 2" flat machine screws provided.




I Position the coat hook 36" (914) above finished floor (hook goes on the inside face of the compartment). Using the hook as a template, drill (2) Ø15/64" pilot holes, 5/8" (16) deep. Secure with the #14 x 5/8" screws provided.



J Position the wall bumper 3" (76) up from the bottom and 3" (76) from the latch side of the door (bumper goes on the outside face of the door). Using the bumper as a template, drill (2) Ø11/64" pilot holes, 5/8" (16) deep. Secure to the door using the #10 x 5/8" screws provided.



K Clean the strike pilaster notched surface using isopropyl alcohol (by others). Remove a dampening strip from the liner and place the top edge 3" (76) down from the top notch; apply pressure to adhere to the pilaster. Remove the second dampening strip from the liner and place the bottom edge 3" (76) up from the bottom notch, and apply pressure to adhere to the pilaster.



10a Door Hardware for Outswing Doors (continued)


Flat Strike at Wall – Outswing

L With the door in the closed position, place the non-notched edge of the flat strike against the wall. The notched edge of the door should fit into the notch on the flat strike. The top edge of the flat strike and door should align along with the front faces.

M Using the flat strike as a template, mark the hole locations on the wall. Remove the flat strike and drill a $\varnothing 1/4"$ hole (min. 2" (51) deep) at each hole location.

N Insert the plastic anchors in all of the holes and secure the flat strike to the wall using the #10 x 2" screws provided.

O Refer to Step G for installing the keeper and Step K for installing the dampening strip.




Flat Strike at Pilaster – Outswing

P With the door in the closed position, place the non-notched edge of the flat strike against the pilaster. The notched edge of the door should fit into the notch on the flat strike. The top edge of the flat strike and door should align along with the front faces.

Q Using the flat strike as a template, mark the hole locations on the pilaster. Remove the flat strike and drill a $\varnothing 11/64"$ hole (min. 1/2" (13) deep) at each hole location.

R Secure the flat strike to pilaster wall using the #10 x 1" screws provided.

S Refer to Step G for installing the keeper and Step K for installing the dampening strip.




11 Urinal Screens with Stirrup Brackets (Standard)

Before installing the urinal screen components, determine the correct location for your application.

A Draw a plumb line on the wall to represent the urinal screen centerline. Measure from the highest point in the room and place a mark on the urinal screen centerline at dimensions "A", "B", and "C" for the respective urinal screen height (see table below).


B Position and center brackets at each mark on the urinal screen centerline. Using the bracket as a template, mark the hole locations on the wall. Remove the bracket and drill a Ø5/16" hole (minimum 2" (51) deep) at each hole location.



C Insert plastic anchors in all holes and secure bracket to the wall with the #14 x 2" screws provided.

D Place the urinal screen at dimension "D" for the respective urinal screen height (see table on right) and insert it into the wall brackets until a 1" (25) gap between the wall and urinal screen is established.

E Using the bracket as a template, drill Ø1/4" holes through the urinal screen at each bracket hole. Secure the urinal screen to the brackets with the #10-24 x 1/2" barrel nuts and #10-24 x 1/2" shoulder screws provided.




	Dim "A"	Dim "B"	Dim "C"	Dim "D"
42" Urinal Screen	24" (610)	39" (991)	54" (1372)	18" (457)
48" Urinal Screen	18" (457)	36" (914)	54" (1372)	12" (305)

11a Urinal Screens with Continuous Stainless Steel Brackets (Optional)

- Before installing the urinal screen components, determine the correct location for your application.
- Brackets are used as templates, but since the hole patterns may be different, the brackets may not be interchangeable.

A Draw a plumb line on the wall to represent the urinal screen centerline. Measure from the highest point in the room and place a mark on the urinal screen centerline at dimension "A" for the respective urinal screen height (see table below).


B Place the bottom of the bracket on the mark and center the opening on the urinal screen centerline. Using the bracket as a template, mark the hole locations on the wall. Remove the bracket and drill a $\text{Ø}5/16"$ hole (minimum 2" (51) deep) at each hole location.



C Insert plastic anchors in all holes and secure bracket to the wall with the #14 x 2" screws provided.

D Place the urinal screen at dimension "B" for the respective urinal screen height (see table on right) and insert it into the wall bracket until a 1" (25) gap between the wall and urinal screen is established.

E Using the bracket as a template, drill $\text{Ø}1/4"$ holes through the urinal screen at each bracket hole. Secure the urinal screen to the bracket with the #10-24 x 1/2" barrel nuts and #10-24 x 3/8" machine screws provided.



	Dim "A"	Dim "B"
42" Urinal Screen	18-1/2" (470)	18" (457)
48" Urinal Screen	12-1/2" (318)	12" (305)